



Features

- Formatted and presented in the shape of a standard incandescent lightbulb with built in driver for easy and direct retrofit
- Anti flicker technology
- Variety of color temperatures; cool white, white, warm white
- Super bright output (up to 82lm/W efficiency)
- Featured in dimmable
- Outstanding thermal solution allows for usage in commercial application
- Effective distribution of light (360 degrees)
- Available in standard base fitting of B22 (bayonet) or E27 (screw) sockets
- Reliable 30,000 hours lifetime
- Full 12 month product warranty

Recommended Applications

- Ideal for general lighting
- Direct replacement for any incandescent or fluorescent bulb



Ordering Information

Ordering Code	Input Voltage	Wattage (W)	Chip Qty	Fitting Diameter	Lumens (lm)
BB-03W01	90/265	3W	3pcs	35*80mm	78
BB-03W02	90/265	3W	3pcs	60*110mm	78
BB-03W04	90/265	3W	3pcs	60*125mm	78
BB-03W05	90/265	3W	3pcs	50*98mm	78
BB-05W01	90/265	5W	5pcs	60*133mm	396
BB-05W02	90/265	5W	5pcs	60*117mm	396
BB-05W04	90/265	5W	5pcs	57*115mm	396
BB-05W05	90/265	5W	5pcs	60*115mm	396
BB-07W01	90/265	7W	7pcs	70*140mm	555
BB-09W01	90/265	9W	9pcs	78*155mm	719
BB-10W01	90/265	10W	10pcs	50*98mm	780
BB-12W01	90/265	12W	12pcs	95*165mm	954
BB-15W01	90/265	15W	15pcs	95*185mm	1196
BB-18W01	90/265	18W	18pcs	95*185mm	1432
BB-24W01	90/265	24W	24pcs	95*250mm	1918



Recyclable



Mercury Free



Long Life



Flicker Free

Enhance safety and improve lighting quality

Our LED technology contains no lead or mercury, it meets the requirements of the Restriction of Hazardous Substances (RoHS) directive adopted by the European Union.

Our robust LED bulbs do not use glass or filaments, reducing the risk of breakage. They also do not emit harmful UV or IR radiation. Because our LED lamps are cooler, light does not cause the discoloration or fading, typical with conventional light sources.

