



Features

- Single tube replacement for traditional T5 or T8 fluorescent lamps
- Anti flicker technology
- Flexible 100-277V AC inline transformer
- Variety of color temperatures; cool white, white, warm white
- Advanced anti-glare lighting diffuser
- Ultra wide beam angle of 160 degrees
- Super bright output (up to 82lm/W efficiency)
- Optional detection systems with motion, sound or infrared sensing
- Reliable 30,000 hours lifetime
- Full 12 month product warranty

Recommended Applications

- Linear fluorescent applications where light performance and energy savings are critical
- Locations that require glass free lamps for safer working conditions
- Cold applications where high light levels and instant light are needed
- Buildings that aim to be mercury free such as healthcare facilities and universities



Ordering Information

Ordering Code	Input Voltage	Lamp Size	Wattage (W)	Lumens (lm)	Sensors Available
TR-09W/06-T5	90/265	T5 0.6M	9	1056	Sound Only
TR-13W/09-T5	90/265	T5 0.9M	13	1584	Sound Only
TR-18W/12-T5	90/265	T5 1.2M	18	2112	Sound Only
TR-10W/06-T8	90/265	T8 0.6M	10	850	Sound / Radar / Infra-red
TR-15W/09-T8	90/265	T8 0.9M	15	1275	Sound / Radar / Infra-red
TR-20W/12-T8	90/265	T8 1.2M	20	1700	Sound / Radar / Infra-red
TR-22W/12-T10	90/265	T10 1.2M	22	2520	Sound Only

Optional automated sensors



Sound & infrared control



Motion control



Quick Installation Guide

