



Features

- Ultra slim series for confined ceiling cavities
- Flexible 90-265V AC inline transformer
- Dimmer capable, compatible with most existing dimmers
- Advanced anti-glare lighting diffuser
- Ultra wide beam angle of 120 degrees
- Available in white and warm white color temperatures
- Stainless steel locking mechanisms
- Durable white powder coated body
- Super bright output (up to 82lm/W efficiency)
- Reliable 30,000 hours lifetime
- Full 12 month product warranty

Recommended Applications

- Indoor down lighting for false ceilings that have a cavity of at least 3" in height.
- Suitable for retrofit replacements (compatible with 4", 5", 6" and 8" cutting holes)
- Suitable for residential, office and retail applications



Ordering Information

Ordering Code	Input Voltage	Wattage (W)	Shape	Lamp Size (mm)	Cutting Diameter (mm)	Lumens (lm)
SL-06W12-RO	90/265	6	Round	120x120x25	105	390
SL-06W12-SQ	90/265	6	Square	120x120x25	105	430
SL-09W14-RO	90/265	9	Round	145x145x25	136	630
SL-09W14-SQ	90/265	9	Square	145x145x25	136	650
SL-12W17-RO	90/265	12	Round	170x170x25	160	860
SL-12W17-SQ	90/265	12	Square	170x170x25	160	1150
SL-15W19-RO	90/265	15	Round	190x190x25	180	1060
SL-15W19-SQ	90/265	15	Square	190x190x25	180	1180
SL-18W22-RO	90/265	18	Round	225x225x25	210	1480
SL-18W22-SQ	90/265	18	Square	225x225x25	210	1600



Quick Installation Guide

Step 1: Make sure the **POWER IS TURNED OFF** at the source to the recessed housing inside which you are installing the products. Once Power has been turned off, remove existing bulb and trim

Step 2: Attach the driver to the existing power terminals, ensuring the wires are completely insulated and away from the cooling fins

Step 3: Squeeze the lock springs on the outside of the fitting and install into place. The springs should hold the light mounting snugly and securely in place

