

# Dalby

## Low profile 8W or LED emergency surface/recessed luminaire/exit sign

Manufactured from Flame-Retardant Polycarbonate, this elegantly designed IP55 Luminaire is suitable for almost any prestigious application.

Dalby can be used for surface or recessed mounting (when recessed only 25mm protrudes below the ceiling) and with the addition of a Self-Adhesive Legend, a simple but attractive Exit sign is created.

The Dalby design also offers an Edge-Lit Exit sign version which can be confidently specified for projects including Hotels and Reception areas.

Dalby's diffuser design incorporates a light-pipe ensuring the LED charge indicator is visible in all modes.

DalbyExit recessed with edge lit exit legend

**Viewing distance 32 metres**



Dalby surface mounted

### Mains Luminaires

Cat No.	Lamp	Lumens	Kg
DAL8	8W 300mm	-	1.35

### Emergency Luminaires

Cat No.	Mode/Lamp	Lumens*	Kg
DAL8/NM3	NM3 8W 300mm	80E	1.80
		120S	
		180H	
DAL8/M3	M3 8W 300mm	80E	2.00
		120S	
		180H	
DAL/LED/M3 <b>NEW</b>	NM/M3 LED	-	1.80

### Slave Luminaires

Cat No.	Mode/Lamp	Lumens*	Kg
DAL8/#/D	Slave 8W Luminaires	275	1.10
DAL/LED/#/D <b>NEW</b>	Slave LED	-	1.10

\* Emergency Lumens

# Specify 24, 50, 110 or 230 Volts AC/DC System Voltage. LED Slaves are suitable for 110V and 220V AC/DC systems

\* For other durations, specify the required time period e.g. /NM3 but for 1 hour duration becomes /NM1

**Dimensions:** Length 355mm x Width 195mm x Depth 70mm

**Legend Size:** 175mm

**Cut out dimensions:** Length 335mm x Width 175mm



SAL2 provides several exit legend options.

**Viewing distance 22 metres**

### Options Suffix:

/H	High Output
/E	Economy Output
/S	Standard Output
/SAL2	Self-adhesive Exit Legend Kit
/HPF	Power Factor Corrected
/HF	High Frequency Ballast
/ES	Electronic Start
/AD	Intelligent Addressable Luminaire
/ST	Self Testing Luminaire
/TS	Push to Test Switch
/EX/L+	Edge-lit Exit Kit
/R	Recessing Kit



IP55/IP20



KM31508