



Holt

A rugged IP65 square luminaire

A robust IP65 luminaire suitable for interior and exterior applications supplied as standard with rear besa and side conduit entries.

Captive screws secure the prismatic diffuser to the white base, with options for an alternative opal diffuser, and black base.

Holt's all polycarbonate housing is robust enough to be used in a wide range of lighting applications and has the advantage of matching models with integral emergency control gear.



Holt with white base and clear diffuser



Holt with black base and opal diffuser

Mains Luminaires

Cat No.	Lamp	Lumens	Kg
HT16B	16W 2D	-	1.10
HT28B	28W 2D	-	2.00
HT211B NEW	2x11W TC-S	-	2.00

Emergency Luminaires

Cat No.	Mode/Lamp	Lumens*	Kg
HT16B/M3	M3 16W 2D	200	3.00
HT28B/M3	M3 28W 2D	270	3.00
HT28B/24/3S	28W Mains + 2x4W T5 NM3	160	3.00
HT211B/M3 NEW	M3 2x11W TC-S (one lamp M3)	180	3.00

Options Suffix:

/AD	Intelligent Addressable Luminaire
/ST	Self Testing Luminaire
/BK	Black Base
/VR	Anti-tamper Screws
/HPF	Power Factor Corrected
/O	Opal diffuser
/PH	Dawn/Dusk Photo Cell
/HF	High Frequency Ballast
/ES	Electronic Start

Slave Luminaires

Cat No.	Mode/Lamp	Lumens*	Kg
HT16B/#/D	Slave 16W 2D	400	1.10
HT28B/#/D	Slave 28W 2D	500	1.50

* Emergency Lumens

Specify 24, 50, 110 or 230 Volts AC/DC System Voltage

* For other durations, specify the required time period e.g. /M3 becomes /M1 for 1 hour duration

Dimensions: Length 255mm x Width 255mm x Depth 90mm

IP65   