

Iona

A robust and attractive square aluminium diecast IP65 exterior bulkhead.

Iona is an impressive range of stylish but robust IP65 square die-cast exterior bulkheads. Suitable for wall and ceiling mounted applications. Iona luminaires are available as standard in black with a toughend polycarbonate opal diffuser secured by vandal resistant screws.

Iona's optional decorative guards/eyelids create a versatile range of architectural luminaires which are available as a mains or 3 hour self contained emergency luminaire.

Other options available to Iona are as a slave luminaire for use with central battery or static inverter systems, with self-test or addressable emergency lighting gear.

An optional Microwave Presence Detector integrally mounted allows presence detection and switching utilising lux level sensing including a time-delay function.

Iona in black with guard option



Iona in silver-grey



Iona in black with eyelid option

Mains Luminaires

Cat No.	Lamp	Lumens	Kg
ION28	1x28W 2D	-	6.0
ION38	1x38W 2D	-	6.0
ION211	2x11W TC-S	-	6.0
ION/LED/230A	LED	-	6.0

Emergency Luminaires

Cat No.	Mode/Lamp	Lumens*	Kg
ION28/M3	M3 28W 2D	270	7.0
ION38/M3	M3 38W 2D	625	7.0
ION211/M3	M3 2 x 11W TC-S 1 lamp M3	390	7.0
ION/LED/M3	M3 LED	-	6.0

Slave Luminaires

Cat No.	Mode/Lamp	Lumens*	Kg
ION28/#/D	Slave 28W 2D AC/DC	500	6.5
ION38/#/D	Slave 38W 2D AC/DC	500	6.5
ION/LED/#/D	Slave LED	-	6.5

* Emergency Lumens

Replace # with AC/DC system Voltage 24, 50, 110 or 230 Volts. LED Slave fittings are suitable for 110V and 220V AC/DC systems.

* For other durations, specify the required time period e.g. /M3 becomes /M1 for 1 hour duration

Dimensions: 360mm x 360mm x 125mm

Options Suffix:

- /SG Silver-Grey Finish
- /EY Eyelid Version
- /GU Guard
- /HPF Power Factor Corrected
- /HF High Frequency Ballast
- /ES Electronic Start
- /AD Intelligent Addressable Luminaire
- /ST Self Testing Luminaire
- /MD Microwave Presence Detector

IP65

