



Calabor

Fully recessed 8W or LED emergency luminaire for interior use

Calabor is an attractive, fully recessed emergency luminaire available in white as standard with brass and chrome as options. The Calabor features a robust galvanised body which recesses fully into the ceiling and only requires a ceiling depth of 90mm. Within the fitting a hinged, removable gear tray facilitates easy fixing and maintenance whilst the front trim plate with a diffuser ensures a neat and attractive finish.

Standard models are supplied with a prismatic polycarbonate diffuser but this can be supplied in opal if preferred.

Calabor is available as a recessed edge-lit exit sign, with an exit fascia manufactured from Plasi-Glas, a light conducting flame retardant plastic almost impossible to distinguish from glass, but with the strength of plastic. Calabor is also available with long life light emitting diode (LED) light sources.

A version with 11 watt TC-S lamps is available for use as a rectangular downlight mains luminaire and combined emergency version.

Calabor in white finish



Calabor in brass finish



Calabor in chrome finish with exit legend

Viewing distance 32 metres


Options Suffix:

- /H High Output
- /E Economy Output
- /S Standard Output
- /BR Brass Finish Fascia
- /CH Chrome Finish Fascia
- /HPF Power Factor Corrected
- /OP Opal diffuser
- /HF High Frequency Ballast
- /ES Electronic Start
- /AD Intelligent Addressable Luminaire
- /ST Self Testing Luminaire
- /EX Exit Version

Mains Luminaires

Cat No.	Lamp	Lumens	Kg
CAL 1x8	8W 300mm	-	2.20
CAL11	11W TC-S	-	2.25
CAL2x11	2x11W TC-S	-	2.40

Emergency Luminaires

Cat No.	Mode/Lamp	Lumens*	Kg
CAL8/NM3 	NM3 8W 300mm	80E	2.70
		120S	
		180H	
CAL2x8/NM3	NM3 2x8W 300mm	240E	3.00
		360S	
		360H	
CAL8/M3	M3 8W 300mm	80E	2.90
		120S	
		180H	
CAL11/8/C3	C3 11W TC-S + 8W 300mm	120S	2.90
CAL/LED/M3 NEW	M3 LED	-	2.20

Slave Luminaires

Cat No.	Mode/Lamp	Lumens*	Kg
CAL8/#/D	Slave 8W AC/DC	275	2.10
CAL11/#/PVR	Mains/Slave 11W Changeover	650	2.10
CAL/LED/#/D NEW	Slave LED	-	2.10

* Emergency Lumens


Specify 24, 50, 110 or 230 Volts AC/DC System Voltage. LED Slaves are suitable for 110V and 220V AC/DC systems

* For other durations, specify the required time period e.g. /NM3 becomes /NM1 for 1 hour duration

Dimensions: Length 410mm x Width 155mm x Depth 90mm

Legend Drop: 175mm

Cut out dimensions: Length 325mm x Width 130mm Ceiling Void 85mm min



KM31508

IP20

