



Idro

Idro in black with guard option



A robust and attractive circular aluminium die-cast IP65 exterior bulkhead, now with LED option.

Idro is a range of robust but versatile circular die-cast IP65 exterior bulkheads. Suitable for wall and ceiling mounted applications, Idro luminaires can be specified with an optional decorative guard, or with an effective and attractive anti-light pollution eyelid or alternatively this luminaire can be selected for use with its toughened polycarbonate opal diffuser alone.

Supplied with vandal resistant screws as standard, Idro is available in black (as standard) or silver-grey, and can be used as a mains or 3 hour integral emergency non-maintained and maintained luminaire.

Other options available to Idro are as a slave luminaire for use with central battery or static inverter systems, with self-test or addressable emergency lighting gear.

An optional Microwave Presence Detector integrally mounted allows presence detection and switching utilising lux level sensing including a time-delay function.

Idro in silver-grey



Idro size A, in black with eyelid option

Mains Luminaires

Cat No.	Lamp	Lumens	Kg
IDR26A NEW	26W TCD Size A TC-D	-	6.0
IDR28B	1x28W 2D Size B	-	6.0
IDR38B	1x38W 2D Size B	-	6.0
IDR211B NEW	2x11W TC-S Size B	-	7.0
IDR/LED/230A NEW	LED Size B	-	6.0

Emergency Luminaires

Cat No.	Mode/Lamp	Lumens*	Kg
IDR28B/M3	M3 28W 2D Size B	270	7.0
IDR38B/M3	M3 38W 2D Size B	625	7.0
IDR211B/M3 NEW	M3 2 x 11W TC-S (1 lamp M3)	390	7.0
IDR/LED/M3 NEW	M3 LED Size B	-	6.3

Slave Luminaires

Cat No.	Mode/Lamp	Lumens*	Kg
IDR26B/#D NEW	Slave 26W TC-D AC/DC Size B	450	6.0
IDR28B/#/D	Slave 28W 2D AC/DC Size B	500	6.0
IDR38B/#/D	Slave 38W 2D AC/DC Size B	500	6.0
IDR/LED/#/D NEW	Slave LED Size B	-	6.0

* Emergency Lumens

Replace # with AC/DC system Voltage 24, 50, 110 or 230 Volts. LED Slave fittings are suitable for 110V and 220V AC/DC systems.

* For other durations, specify the required time period e.g. /M3 becomes /M1 for 1 hour duration

Dimensions: Size A: 260mm Ø x 115mm Depth

With Optional Guard/Eyelid Depth 155mm

Size B: 360mm Ø x 130mm Depth

Options Suffix:

/SG	Silver-Grey Finish
/EY	Eyelid Version
/GU	Guard
/HPF	Power Factor Corrected
/HF	High Frequency Ballast
/ES	Electronic Start
/AD	Intelligent Addressable Luminaire
/ST	Self Testing Luminaire
/MD	Microwave presence detector (size B only)

IP65    