

Kandel

Circular surface or semi-recessed IP54 luminaire

An attractive range of circular IP54 white polycarbonate luminaires, Kandel can be specified as a mains or emergency luminaire with integral emergency gear, using either 2D or TC-S compact fluorescent lamps. Kandel is now available as an energy saving, maintenance free, LED luminaire utilising the latest LED technology. This allows this stylish luminaire to be confidently specified for most applications.

Kandel can be surface mounted or semi-recessed using an attractive range of high quality surface trims are available in white, brass or chrome which transform Kandel into a stylish range of mains and emergency luminaires.

The optional choice of opal, green, red or blue halo effects for Kandel luminaires allows them to be confidently specified for several applications where a certain colour theme is required such as hotels, hospitals, restaurants etc.

This is particularly effective when combined with the new wide angled reflecting trim.

Installation and maintenance is simplified due to the design of the twist-and-lock diffuser, which is supplied in opal as standard with an alternative clear diffuser available.



Kandel recessed



Kandel white trim

Mains Luminaires

Cat No.	Lamp	Lumens	Kg
KN16	16W 2D	-	0.50
KN28	28W 2D	-	0.50
KN38	38W 2D	-	0.50
KN211 NEW	2 x 11W TC-S	-	0.50
KN/LED/230A NEW	LED	-	0.50

Emergency Luminaires

Cat No.	Mode/Lamp	Lumens*	Kg
KN16/NM3	NM3 16W 2D	160	2.90
KN16/M3	M3 16W 2D	160	3.00
KN28/NM3	NM3 28W 2D	280	3.00
KN28/M3	M3 28W 2D	280	3.00
KN28/24/3S	Mains 28W + NM3 2x4W 150mm	160	2.70
KN211/M3 NEW	2 x 11W TC-S One lamp in M3	180	2.30
KN/LED/M3 NEW	M3 LED	-	2.70

Slave Luminaires

Cat No.	Mode/Lamp	Lumens*	Kg
KN16/#/D	Slave 16W 2D	420	2.30
KN28/#/D	Slave 28W 2D	650	2.30
KN38/#/D	Slave 38W 2D	650	2.30

* Emergency Lumens

Specify 24, 50, 110 or 230 Volts AC/DC System Voltage. LED

* For other durations, specify the required time period e.g. /NM3 becomes /NM1 for 1 hour duration

Dimensions reflective trim: Ø 520mm x Depth 85mm

Dimensions: Ø 360mm x Depth 85mm

Cut out dimensions: Ø 335mm x 50mm Minimum Ceiling Void

Options Suffix:

/AD	Intelligent Addressable Luminaire
/ES	Electronic Start
/R	Recessing Kit
/CD	Clear Diffuser
/HF	High Frequency
/HPF	Power Factor Correction
/ST	Self Testing Luminaires

Surface Trims Options Suffix:

KN/BR	Brass Surface Trim
KN/CH	Chrome Surface Trim
KN/WH	White Surface Trim

Reflecting Trims Options Suffix:

KRT/BR	Brass Reflecting Trim
KRT/CH	Chrome Reflecting Trim
KRT/WH	White Reflecting Trim

Back Light Effect Options

/BU	Blue Halo Effect
/GN	Green Halo Effect
/RD	Red Halo Effect
/OP	Opal Halo Effect