



Multia

A stylish range of compact fluorescent/Metal Halide Discharge downlights



Multia is a comprehensive range of downlighters offering a variety of options for almost every application.

Available from 18W to 42W in both single and twin lamp versions. Multia is supplied with a white bezel as standard with inter-changeable brass or chrome options which enables the Multia to suit most interior decor.

Single 70/150W Metal Halide versions allow this luminaire to be specified in most commercial and retail environments.

Additional optional attachments include an attractive floating glass, IP44 opal cover and a range of polycarbonate emergency drop legends which creates a complete and quality range of recessed downlight luminaires.

Emergency options, for all compact fluorescent versions, are available using a remote box which contains BSI approved Perferm™ emergency control gear, designed to operate low Mercury compact fluorescent lamps.

Multia also offers a range of mains HQI discharge downlights with integral control gear for 70W and 150W lamps.

Mains Luminaires

Cat No.	Lamp	Lumens	Kg
MU18	18W TC-D	–	2.42
MU218	2 x 18W TC-D	–	3.25
MU26	26W TC-D	–	2.42
MU226	2 x 26W TC-D	–	3.25
MU32	32W HF TC-T	–	2.28
MU42	42W HF TC-T	–	2.36
MU232 NEW	2 x 32W HF TC-T	–	3.25
MU242 NEW	2 x 42W HF TC-T	–	3.25
MU70 NEW	1 x 70W HQI-TS	–	2.50
MU150 NEW	1 x 150W HQI-TS	–	2.50

Emergency Luminaires (Incorporating Perferm™ Technology)

Cat No.	Mode/Lamp	Lumens*	Kg
MU18/M3	M3 18W TC-D	276	2.42
MU218/M3	M3 2 x 18W TC-D	276	3.25
MU26/M3	M3 26W TC-D	324	2.42
MU226/M3	M3 2 x 26W TC-D	324	3.25
MU32/M3	M3 32W HF TC-T	480	2.28
MU42/M3	M3 42W HF TC-T	416	2.36
MU232/M3 NEW	M3 2 x 32W TC-T	480	3.30
MU242/M3 NEW	M3 2 x 42W TC-T	416	3.40

Mains/Slave Luminaires

Cat No.	Mode/Lamp	Lumens*	Kg
MU218/PVR/# NEW	2 x 18W TC-D One lamp in emergency	390	3.55
MU226/PVR/# NEW	2 x 26W TC-D One lamp in emergency	400	3.55
MU232/PVR/# NEW	2 x 32W TC-T One lamp in emergency	580	3.55
MU242/PVR/# NEW	2 x 42W TC-T One lamp in emergency	760	3.55

LAMPS NOT INCLUDED

* Emergency Lumens

Specify 24, 50, 110 or 230 Volts AC/DC System Voltage

* For other durations, specify the required time period e.g. /M3 becomes /M1 for 1 hour duration

^ Supplied with remote mounted metal halide control gear

Dimensions: Ø 226mm x 198mm (Minimum Ceiling Void)

Cut-Out (All Versions): Ø 208mm

* This weight does not include remote gear box, add 2.1kg

Options Suffix:

/AD	Intelligent Addressable Luminaire
/ES	Electronic Start
/HF	High Frequency
/HPF	Power Factor Corrected
/ST	Self Testing Luminaire
/L+	Drop Legend (Replace + with Required Legend Panel)
/TB	Turbo Louvre

Trims:

MU/BR	Brass trim
MU/CH	Chrome trim

Drop Glass:

DG/WH	Drop glass with White trim
DG/BR	Drop glass with Brass trim
DG/CH	Drop glass with Chrome trim

IP Cover:

IP/WH	IP44 White cover
IP/BR	IP44 Brass cover
IP/CH	IP44 Chrome cover

IP20/44



The informed choice.



White trim turbo louvre



Chrome trim



Brass trim with legend



Chrome trim drop glass



IP44 Brass trim