



# Odet

## Emergency floodlighting unit

Odet emergency floodlights incorporate a British Standard Approved Constant Voltage Charger. The chargers are fitted with thermal, current and short circuit protection devices. A low voltage disconnect circuit to prevent the batteries entering a deep discharge state in the event of prolonged power failure, maximising battery life.

Batteries are maintenance free, sealed lead acid types with a life expectancy of five years under normal conditions. The robust but stylish sheet steel enclosure is finished in a light grey epoxy coating. Odet is also available with an IP65 polycarbonate enclosure, for external requirements. We have extended the range to include a 2x55W NM3 version.

Odet is available as a deluxe version utilising 20 Watt and 50 Watt dichroic halogen lamps (not supplied). The various beam angles enable the client to tailor the light distribution to their specific requirements. The heads enable the lamps to be adjusted both horizontally and vertically giving total flexibility. Available as standard in white finish, this stylish emergency luminaire is a popular choice for shopping malls and most interior applications.

An optional 14 minute timer enables Odet to continue to operate in the emergency mode after the main supply has been reinstated allowing discharge luminaires to re-ignite and provide a suitable light output.



ODS 20/NM1/TH



Odet IP65



ODS Deluxe



ODS 55/NM3/TH

### Emergency Luminaires

Cat No.	Mode/Lamp	Lumens	Kg
ODS20/NM1/TH	NM1 2x20W/TH	2x 340	5.88
ODS20/NM3/TH	NM3 2x20W/TH	2x 340	7.00
ODS21/NM1	NM1 2x21W	2x 280	5.88
ODS21/NM3	NM3 2x21W	2x 280	7.00
ODS55/NM1/TH	NM1 2x55W TH	2x 900	7.50
ODS55/NM3/TH†	NM3 2x55W TH	2x 900	16.00
ODS/DELUXE	20/50W* Dichroic	-	7.00

### Slave Luminaires

Cat No.	Mode/Lamp	Lumens	Kg
ODS20/#D <b>NEW</b>	Slave 2 x20W	2x 340	3.00
ODS21/#D <b>NEW</b>	Slave 2 x 21W	2x 280	3.00
ODS55/#D <b>NEW</b>	Slave 2 x 55W	2x 900	3.00
ODS/DELUXE/#D <b>NEW</b>	Slave 20/50W *	-	3.20

\* Deluxe versions give 3 hours emergency duration when used with 20W lamps and a 1 hour emergency duration when used with 50W lamps (lamps not supplied)

\* Odet Slaves are suitable for 110V and 220V AC/DC supplies

\* Emergency Lumens

† This product is supplied with the batteries packed separately

**Dimensions:** 20 and 21W (NM1 & NM3) 55W (NM1) Length 315mm x Height 310mm x Depth 110mm  
55W NM3 Length 440mm x Height 315mm x Depth 110mm

**Dimensions IP65 Version:** Length 400mm x Height 400mm x Depth 135mm

**Dimensions Deluxe Version:** Length 315mm x Height 200mm x Depth 75mm

### Options Suffix:

- /AD Intelligent Addressable Luminaire (not available in deluxe version)
- /ST Self Testing Luminaire (not available in deluxe version)
- /IP65 Weatherproof Enclosure
- /TM14 14 Minute Timer Delay Unit for use with Discharge Lamp Schemes

IP20/65 