



Pescara

Fluorescent exit sign for internal and external use

The Pescara range of fluorescent single and double sided exit signs are manufactured from sheet steel and finished in a choice of either white, black, brass or chrome. Pescara's many features include a hinged internal steel gear tray, rear centre Besa entry, keyhole mounting slots and an opal threshold downlight panel to illuminate the area below the sign.

The double sided version of Pescara has a central top Besa entry for ease of fixing. The double-sided sign is no deeper than the standard Pescara exit sign and so co-ordinates with other Pescara models.

A special U shaped gear tray allows even illumination of both legend panels and an opal downlight panel ensures that illumination is also directed below the sign to the escape route and the door threshold.

The Cinema version of Pescara exit sign is fitted with a fret-cut legend panel to reduce light emission. They are designed for use in Theatres, Cinemas, School Halls and Discotheques.

The IP65 rated Pescara is of robust construction making it suitable for external and internal use. It is suitable for car parks, sports stadiums, livestock markets and many other applications.

Non-maintained, maintained and sustained (combined) models are BSI approved to EN60598, and all models are CE and F marked.

The legend panel can be removed from either end of the sign via removable endcaps making Pescara suitable for close fitting into corners where necessary.

Viewing distance
40 metres



IP65 Pescara




Pescara with
fret cut legend

Mains Luminaires

Cat No.	Lamp	Lumens	Kg
PES8	8W 300mm Single Sided	-	2.60
PED8	8W 300mm Double Sided	-	2.60

Emergency Luminaires

Cat No.	Mode/Lamp	Lumens*	Kg
PES8/NM3	 NM3 8W 300mm Single Sided	120	2.75
PES8/M3	 M3 8W 300mm Single Sided	120	3.00
PES8/C3	 C3 8W 300mm Single Sided	120	3.00
PED8/NM3	NM3 8W 300mm Double Sided	120	2.75
PED8/M3	M3 8W 300mm Double Sided	120	3.00

Slave Luminaires

Cat No.	Mode/Lamp	Lumens*	Kg
PES8/#/D	Slave 8W Exit Sign Single Sided	275	2.50
PED8/#/D	Slave 8W Exit Sign Double Sided	275	2.50

* Emergency Lumens

Specify 24, 50, 110 or 230 Volts AC/DC System Voltage

* For other durations, specify the required time period e.g. /NM3 becomes /NM1 for 1 hour duration

Dimensions: Length 385mm x Width 200mm x Depth 95mm (Low Profile 65mm)

Dimensions IP65 Version: Length 445mm x Width 225mm x Depth 95mm

Options Suffix:

/C	Fret Cut Legend
/BK	Black Finish
/BR	Brass Finish
/CH	Chrome Finish
/E	Economy Version
/IP65	IP65 Version (Does not have a Downlight Panel)
/LP	Single sided signs available in low profile
/VR	Anti-tamper Screws
/HPF	Power Factor Corrected
/HF	High Frequency Ballast
/ES	Electronic Start
/AD	Intelligent Addressable Luminaire
/ST	Self Testing Luminaire
/TS	Push to Test Switch
/RAB	Right angled mounting bracket

IP20/65



KM31508



For all Legend details
See Page 65