



Tiel

IP65 single or double sided exit sign

Tiel is a robust IP65 ceiling mounted single or double sided white polycarbonate exit sign. Suitable for surface or semi-recessed installations.

Its IP65 rating and optional tamper resistant screws, make the Tiel a unique single or double sided sign for all public areas.

Tiel is supplied complete with two self-adhesive legends as standard (please specify) so that the installer can create either a single sided or double sided sign.



Viewing distances
28 metres




Tiel recessed

Mains Luminaires

Cat No.	Lamp	Lumens	Kg
TI8	1x8W 300mm	-	0.90
TI2x8	2x8W 300mm	-	0.90
TI11	11W TC-S	-	0.90

Emergency Luminaires

Cat No.	Mode/Lamp	Lumens*	Kg
TI8/NM3	NM3 8W 300mm	80E 120S 180H	1.20
TI8/M3	 M3 8W 300mm	80E 120S 180H	1.45
TI2X8/NM3	NM3 2X8W 300mm	150S 250H	1.70
TI/LED/M3 NEW	NM3/M3 LED	-	1.20

Slave Luminaires

Cat No.	Mode/Lamp	Lumens*	Kg
TI8/#/D	Slave 8W	275	0.85
TI/LED/#D NEW	Slave LED	-	0.90

* Emergency Lumens

Specify 24, 50, 110 or 230 Volts AC/DC System Voltage. LED Slaves are suitable for 110V and 220V systems.

* For other durations, specify the required time period e.g. /NM3 becomes /NM1 for 1 hour duration

Dimensions: Length 350mm x Width 108mm x Depth 204mm

Cut out dimensions: Length 330mm x Width 90mm

Options Suffix:

/E	Economy Output
/S	Standard Output
/H	High Output
/TI/WH	White Finished Semi-recess Trim
/TI/BR	Brass Finished Semi-recess Trim
/TI/CH	Chrome Finished Semi-recess Trim
/VR	Anti-tamper Screws
/HPF	Power Factor Corrected
/HF	High Frequency Ballast
/ES	Electronic Start
/AD	Intelligent Addressable Luminaire (Non-Maintained Only)
/ST	Self Testing Luminaire (Non-Maintained Only)
/TS	Push to Test Switch

IP65      

