



Leah

Leah is an attractive circular IP65 robust polycarbonate luminaire available for wall or ceiling mounting.

Leah offers a choice of 2D, T5c and TC-S energy-saving lamps for mains lighting with optional integral 3 hour emergency versions including slave.

Supplied as standard with a hinged geartray, white base and opal diffuser, this high quality elegant luminaire provides a reliable and effective solution for most indoor and outdoor applications.

Leah with large white trim



Optional elegant trims are available which create an impressive diffused halo-effect enabling this stylish range of luminaires to be considered for luxurious or challenging applications including hotels, universities, shower areas and stairwells. Alternatively, the Leah can be used as a semi-recessed luminaire when using the narrower version of the two attractive trims.

Leah is suitable for self-test emergency lighting and can be supplied with emergency gear for intelligent addressable systems.

Leah with narrow white trim



Leah without trim



Mains Luminaires

| Cat No. | Lamp | Lumens | Kg |
|---------|------------------|--------|------|
| LE28 | 28W 2D | - | 2.70 |
| LE38 | 38W 2D | - | 2.70 |
| LE40 | 40W T5c Circular | - | 2.70 |
| LE211 | 2 x 11W TCS | - | 2.70 |

Emergency Luminaires

| Cat No. | Mode/Lamp | Lumens* | Kg |
|----------|-------------------------------|---------|------|
| LE28/M3 | M3 28W 2D | 384 | 3.60 |
| LE38/M3 | M3 38W 2D | 625 | 3.60 |
| LE40/M3 | M3 40W T5c Circular | 370 | 3.60 |
| LE211/M3 | 2 x 11W TC-S (One lamp in M3) | 390 | 3.60 |

Slave Luminaires

| Cat No. | Mode/Lamp | Lumens* | Kg |
|----------|------------------------|---------|------|
| LE28/#D | Slave 28W 2D | 500 | 2.60 |
| LE38/#D | Slave 38W 2D | 500 | 2.60 |
| LE40/#D | Slave 40W T5c Circular | 990 | 2.60 |
| LE211/#D | Slave 2 x 11W TCS | 380 | 2.60 |

* Emergency Lumens

Specify 24, 50, 110 or 230 Volts AC/DC System Voltage

* For other durations, specify the required time period e.g. /M3 becomes /M1 for 1 hour duration

No Trim Version Dimensions: Ø 395mm x 120mm

Narrow Trim Version Dimensions: Ø 440mm x 120mm

Broad Trim Version Dimensions: Ø 520mm x 120mm

Recess Cut out: Ø 357mm

Options Suffix:

| | |
|-----|-----------------------------------|
| /ST | Self Testing Luminaire |
| /AD | Intelligent Addressable luminaire |
| /HF | High Frequency |
| /NT | Narrow Trim |
| /WT | Wide Trim |
| /OP | Opal Halo Base |